



RECESSED DOWNLIGHTS

Recessed Adjustable COB Downlight 30W

Large recessed COB downlight with a tilting head, for directed light from the ceiling.

— Powder coated finish


APPLICATIONS

Shops and showrooms, Hotel lobbies and corridors, Restaurants, Offices and meeting rooms, Reception areas

Code **LUZ-CB30**

Light colour

3000 / 6500 K



Power


30 W



85-265V AC

Light output

2750 lm



92 lm/W

Beam angle

40°



2.2 m wide pool from 3 m high.

Protection

IP20



For dry indoor rooms.

Cut out

D190 mm



Hole size in the ceiling.

Colour rendering

Ra 80



Meets the Ra 80 minimum for most indoor work.

Dimming

Not dimmable



On / off

Specifications

LIGHT

Luminous flux	2750 lm
Colour temperature	3000K or 6500K
Colour rendering	Ra 80
Beam angle	40°

ELECTRICAL

Power	30 W
Input	85-265V AC
Dimming	Not dimmable
Driver	Included
Protection class	II

BUILD AND INSTALLATION

Size	D225 × 38 mm
Cut out	D190 mm
Material	Aluminium and PC
Finish	White
IP rating	IP20
Ambient temperature	-20 to 50 °C
Mounting	Recessed, tilting head

Versions

LUZ-CB30 CCT: 3000K

LUZ-CB30 CCT: 6500K

