



RECESSED DOWNLIGHTS

Deep Recessed Downlight 6W

Deep recessed round downlight with the light source set back in the housing to reduce glare.

— Spring clips


APPLICATIONS

Living areas and kitchens, Hallways and corridors, Offices, Shops, Hotel rooms

Code **LUZ-DA186**

Light colour

3000 / 4000 / 6500 K



Selectable colour temperature.

Power

6 W



85-265V AC

Beam angle

90°



6.0 m wide pool from 3 m high.

Protection

IP20



For dry indoor rooms.

Cut out

D63 mm



Hole size in the ceiling.

Colour rendering

Ra 80



Meets the Ra 80 minimum for most indoor work.

Specifications

LIGHT

Colour temperature	3000K, 4000K, 6500K or CCT selectable
Colour rendering	Ra 80
Beam angle	90°

ELECTRICAL

Power	6 W
Input	85-265V AC
Power factor	0.6

BUILD AND INSTALLATION

Size	D74 × 52 mm
Cut out	D63 mm
Material	Aluminium and PP
IP rating	IP20
Mounting	Recessed

Versions

LUZ-DA186	CCT: 3000K
LUZ-DA186	CCT: 6500K

LUZ-DA186	CCT: 4000K
LUZ-DA186	CCT: CCT selectable

Works with

LED Driver 6W for Downlight DA186

LED Board 6W CCT for Downlight DA186

