



FLOODLIGHTS

Modular Floodlight 400W, 6500K

Modular LED floodlight for large outdoor areas.


- Bracket held by double safety screws, so the aim stays set over time

APPLICATIONS

Sports fields and courts, Large car parks, Ports and industrial yards, Building facades

Code **LUZ-F7400-65**

Light colour
6500 K



Cool white

Power
400 W



100-240V AC

Light output
48000 lm



120 lm/W

Beam angle
60 to 120°



Wide spread for general light.

Protection
IP65



Outdoor use, rain and dust proof.

Colour rendering
Ra 70



For outdoor and industrial areas.

Specifications

LIGHT

Luminous flux	48000 lm
Efficacy	120 lm/W
Colour temperature	6500K
Colour rendering	Ra 70
Beam	120 × 60 degrees
Lifetime	>54000 h (L70 at 30 °C)

ELECTRICAL

Power	400 W
Input	100-240V AC
Driver	Constant current, isolated
Power factor	≥0.95
Protection class	I
Surge protection	5 kV

BUILD AND INSTALLATION

Size	565 × 545 × 65 mm
Weight	9.4 kg
Material	Aluminium alloy housing, PC lens
IP rating	IP65
IK rating	IK10
Ambient temperature	-40 to 50 °C
Cable	0.2 to 0.3 m

