



LUZ15 MINI MAGNETIC SYSTEM, 48V

Magnetic Cone Pendant 8W

Magnetic cone pendant on a cable, for the LUZ15 track.


APPLICATIONS

Dining tables and kitchen islands, Restaurants and bars, Shop counters, Hotel lobbies

Code **LUZ-P1904-8**

Light colour

3000 K



Warm white

Power

8 W

Light output

572 lm



72 lm/W

Beam angle

30°



1.6 m wide pool from 3 m high.

Protection

IP20



For dry indoor rooms.

Colour rendering


Ra 90+



Accurate colours, for shops, galleries and hotels.

Dimming

Dimmable



Specifications

LIGHT

Luminous flux	572 lm
Colour temperature	3000K
Colour rendering	Ra 90+
Beam angle	30°

ELECTRICAL

Power	8 W
Dimming	Dimmable
Protection class	III

BUILD AND INSTALLATION

Size	L220, shade D90 × 95 mm
Weight	0.28 kg
Finish	Black
IP rating	IP20

Works with

LUZ-RS20-2M	Recessed Magnetic Track, 2 m
LUZ-SP192-2M	Trimless Recessed Magnetic Track, 2 m
LUZ-RL48111-DIM	Track Driver 150W, 48V, 0-10V Dimmable
LUZ-PF-01	Power Feed Connector
LUZ-FTJ-03	Flexible Corner Connector
LUZ-VRS-20	Vertical Corner for Recessed Track RS20
LUZ-VSS-19	Vertical Corner for Surface Track SS19

LUZ-SS19-2M	Surface Magnetic Track, 2 m
LUZ-RL48150	Track Driver 150W, 48V
LUZ-IJ-01	Straight Connector
LUZ-CJT-04	Horizontal Corner Connector
LUZ-CRS-20	Horizontal Corner for Recessed Track RS20
LUZ-CSS-19	Horizontal Corner for Surface Track SS19

