



LUZ15 MINI MAGNETIC SYSTEM, 48V

Magnetic Track Spot 3W


Small magnetic spot with an adjustable head, for the LUZ15 track.

APPLICATIONS

Shop displays, Galleries and artwork, Shelves and display cases, Restaurants and bars

 Code **LUZ-RL1903**

Light colour


3000 K


Warm white

Power

3 W

Light output

193 lm


64 lm/W

Beam angle

23.7°


1.3 m wide pool from 3 m high.

Protection

IP20



For dry indoor rooms.

Colour rendering

Ra 90+


Accurate colours, for shops, galleries and hotels.

Dimming

Dimmable


Specifications

LIGHT

Luminous flux	193 lm
Colour temperature	3000K
Colour rendering	Ra 90+
Beam angle	23.7°

ELECTRICAL

Power	3 W
Dimming	Dimmable
Protection class	III

BUILD AND INSTALLATION

Size	L150, head D22 × 50 mm
Weight	0.06 kg
Finish	Black
IP rating	IP20
Adjustment	Tilts 180°, rotates 350°

Works with

LUZ-RS20-2M	Recessed Magnetic Track, 2 m
LUZ-SP192-2M	Trimless Recessed Magnetic Track, 2 m
LUZ-RL48111-DIM	Track Driver 150W, 48V, 0-10V Dimmable
LUZ-PF-01	Power Feed Connector
LUZ-FTJ-03	Flexible Corner Connector
LUZ-VRS-20	Vertical Corner for Recessed Track RS20
LUZ-VSS-19	Vertical Corner for Surface Track SS19

LUZ-SS19-2M	Surface Magnetic Track, 2 m
LUZ-RL48150	Track Driver 150W, 48V
LUZ-IJ-01	Straight Connector
LUZ-CJT-04	Horizontal Corner Connector
LUZ-CRS-20	Horizontal Corner for Recessed Track RS20
LUZ-CSS-19	Horizontal Corner for Surface Track SS19

