



LUZ15 MINI MAGNETIC SYSTEM, 48V

Magnetic Globe Light 3W

Magnetic glass globe light for the LUZ15 track.


APPLICATIONS

Restaurants and bars, Hotel lobbies and corridors, Living and dining areas, Shops

Code **LUZ-RL1980**

Light colour

3000 K



Warm white

Power


3 W



48V DC

Light output

186 lm



62 lm/W

Beam angle

113°



Wide spread for general light.

Protection

IP20



For dry indoor rooms.

Colour rendering


Ra 90+



Accurate colours, for shops, galleries and hotels.

Dimming

Dimmable



With a dimmable 48V driver.

Specifications

LIGHT

Luminous flux	186 lm
Colour temperature	3000K
Colour rendering	Ra 90+
Beam angle	113°

ELECTRICAL

Power	3 W
Voltage	48V DC
Dimming	Dimmable with a dimmable 48V driver
Protection class	III

BUILD AND INSTALLATION

Size	globe D80, L150 mm
Finish	Black
IP rating	IP20

Works with

LUZ-RS20-2M	Recessed Magnetic Track, 2 m
LUZ-SP192-2M	Trimless Recessed Magnetic Track, 2 m
LUZ-RL48111-DIM	Track Driver 150W, 48V, 0-10V Dimmable
LUZ-PF-01	Power Feed Connector
LUZ-FTJ-03	Flexible Corner Connector
LUZ-VRS-20	Vertical Corner for Recessed Track RS20
LUZ-VSS-19	Vertical Corner for Surface Track SS19

LUZ-SS19-2M	Surface Magnetic Track, 2 m
LUZ-RL48150	Track Driver 150W, 48V
LUZ-IJ-01	Straight Connector
LUZ-CJT-04	Horizontal Corner Connector
LUZ-CRS-20	Horizontal Corner for Recessed Track RS20
LUZ-CSS-19	Horizontal Corner for Surface Track SS19

